

FOR COATING, RESINS, AND RELATED MATERIALS

Prepared by: DG
Last Revision Date: 00-00-00
Manufacturer: MARCUS PAINT COMPANY
Address : 235 EAST MARKET STREET

Date: 05-16-20

LOUISVILLE KY 40202

For: WIRECRAFTERS, INC.
6208 STRAWBERRY LANE
LOUISVILLE KY 40214

Telephone: 502/584-0303 EMERGENCY PHONE IN KY 1-800-722-5725
MSDS Last Prepared: NONE OUTSIDE KY 1-800-854-6813

SECTION I PRODUCT IDENTIFICATION

Manufacturer's Code Identification: SP-10651 Revision
Product Class: EQUIPTO'S ROYAL BLUE AQUA MAR W/R AIR DRY ENAMEL
Trade Name: AQUA MAR

SECTION II HAZARDOUS INGREDIENTS

01 CAS# 1333-86-4
CARBON BLACK
PCT BY WT: .132

EXPOSURE LIMIT:
ACGIH-TLV (TWA) 3.5 MG/M3
OSHA-PEL (8 HR. TWA) 3.5 MG/M3
IARC RATING 2B(POSSIBLY CARCINOGENIC TO HUMANS)

02 CAS# 6846-50-0
TXIB
PCT BY WT: 1-5

03 TITANIUM DIOXIDE CAS# 13463-67-7
PCT BY WT: 1-5

This product contains one or more reported carcinogens or suspected
carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits
recommended column.

00026501

MARCUS PAINT COMPANY
MATERIAL SAFETY DATA SHEET

Page 2

SP-10651
AQUA MAR

This product contains pigments which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

SECTION III PHYSICAL DATA

Boiling Range: High- N/A Low- N/A
Vapor Pressure: N/A
Vapor Density: N/A
Evaporation Rate: N/A
Weight per Gallon: 8.66
Specific Gravity: 1.04
% Volatile by Weight: 60.90
VOC: .518 lbs/gal 62.071 grams/liter
Physical State: N/A
Appearance: N/A
Odor: N/A
Odor Threshold: N/A
pH: N/A
Freezing Point: N/A
Water Solubility: N/A
Coefficient of Water/Oil Distribution: N/A
Mechanical Impact Explosion: N/A
Static Electricity Explosion: N/A

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flammability Classification: Class 2 DOT: Not Regulated
Actual Flashpoint TCC: 135.0 F
Explosion Level: Lower- N/A Upper- N/A
Upper Flammability Limit: Not applicable
Lower Flammability Limit: N/A
Auto Ignition Temperature: N/A
Flame Extension: N/A
Dot#: N/A

SPECIAL FIRE FIGHTING PROCEDURES

Clear fire area of unprotected personnel. Containers that are exposed to intense heat should be cooled with water. Avoid spreading burning liquid with the water used for cooling purposes. Do not enter fire area without protective gear. Fight fire from safe distance or a protected location.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Vapors may be heavier than air and may travel along the ground before ignition/flashback to vapor source. Keep welding or cutting equipment away from product.

SECTION V HEALTH HAZARD DATA

"EFFECTS OF EXCESSIVE OVEREXPOSURE"

Reports have associated repeated and prolonged occupational overexposure to

00026501

SP-10651
AQUA MAR

MARCUS PAINT COMPANY
MATERIAL SAFETY DATA SHEET

Page 3

solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

ACUTE EFFECTS OF OVEREXPOSURE

"EFFECTS OF ACUTE OVEREXPOSURE"

Based on the presence of components (O1) INHALATION-Dust concentrations above the PEL may cause temporary upper respiratory tract discomfort.

"EFFECTS OF CHRONIC OVEREXPOSURE"

Based on the presence of components (O1) No known adverse chronic health effects, but unnecessary exposure to any chemical should be avoided.

"FIRST AID"

EYE CONTACT: Flush with luke warm water for 15 minutes. Seek physician immediately or call emergency number listed in Section I.

SKIN CONTACT: Remove contaminated clothing promptly and rinse effected area with plenty of water. Launder contaminated clothing before reuse. Contact a physician immediately or call emergency number listed in Section I.

INHALATION: Remove exposed individual to fresh air. Restore breathing if required. Contact a physician immediately or call emergency number listed in Section I.

INGESTION: Rinse mouth immediately. Give exposed individual 6 to 8 ounces of liquid if individual can swallow. (Never give anything by mouth to an unconscious person.) DO NOT INDUCE VOMITING unless advised by a physician. Contact a physician immediately or call emergency number listed in Section I.

SECTION VI FIRE-FIGHTING MEASURES

"HAZARDOUS POLYMERIZATION"

Due to the presence of some component(s) Will not occur.

"STABILITY"

Due to the presence of some component(s) This product is stable.

SECTION VII ACCIDENTAL RELEASE MEASURES

"STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED"

Shut off and eliminate all ignition sources. Stay upwind and away from spill unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Cover with inert material to reduce fumes. Keep out of drains, sewers or waterways. Contact fire authorities. Notify local health and pollution control agencies. Call spill response teams if large spill.

"WASTE DISPOSAL METHOD"

Dispose of product in accordance with applicable local, county, state and federal regulations.

SECTION VIII HANDLING AND STORAGE

MARCUS PAINT COMPANY takes no responsibility for determining what measures

are required for personal protection in any specific application.

"PROTECTIVE EYEWEAR"

Avoid contact with eyes. Wear goggles if there is likelihood of contact with eyes. (Consult your safety equipment supplier.) Eyewash stations and safety showers should be readily available in use and handling areas.

"PROTECTIVE GLOVES"

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact. (Consult your safety equipment supplier.)

"HYGIENIC PRACTICES"

Wash hands thoroughly before eating and using washroom.

"RESPIRATORY PROTECTION"

In outdoor or open areas use (NIOSH/MSHA approved) mechanical filter respirator to remove solid airborne particles of overspray during spray application. In restricted ventilation areas use (NIOSH/MSHA approved) chemical-mechanical filters designed to remove a combination of particulate and gas and vapor. In confined areas use (NIOSH/MSHA approved) air line type respirators or hoods. Respiratory protection may also be necessary in any later manufacturing operations in which the product may become airborne in the form of vapor or dust.

Eyewash stations and safety showers should be readily available in use and handling areas.

"VENTILATION"

Use ventilation as required to control vapor/dust concentrations. Avoid prolonged or repeated breathing of vapors/dust. If exposures exceed TLV, use NIOSH approved respirator to prevent overexposures.

SECTION IX SPECIAL PRECAUTIONS

"HANDLING AND STORING PRECAUTIONS"

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. Do NOT smoke in storage areas.

"OTHER IMPORTANT INFORMATION"

THE INFORMATION CONTAINED HEREIN IS INFORMATION RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES AND IS BELIEVED TO BE RELIABLE. MARCUS PAINT COMPANY MAKES NO EXPRESS OR IMPLIED WARRANTIES REGARDING THE ACCURACY HEREOF OR THE SUITABILITY OF THE PRODUCT FOR ANY APPLICATION BY USER, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE.

SECTION X SECTION 313 TOXIC CHEMICALS

There are no SARA reportable materials in this product.