

26258

PRODUCT NAME: YELLOW AQUA MAR W/R A.D. ENAMEL
PRODUCT CODE: SP-13170

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Marcus Paint Company
ADDRESS : 235 E. Market St.
Louisville, KY 40202

EMERGENCY PHONE IN KY : 1-800-722-5725
OUTSIDE KENTUCKY : 1-800-854-6813

DATE PRINTED : 1/13/2011
CORPORATE PHONE : 502-584-0303

===== SECTION II - HAZARDOUS INGREDIENTS/SARA 313 INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	WEIGHT%
DIPROPYLENE GLYCOL N-PROPYL ETHER OSHA-PEL (8 hr. TWA) = NOT ESTABLISHED ACGIH-TLV (TWA) = NOT ESTABLISHED	29911-27-1	7.0
P TITANIUM DIOXIDE OSHA-PEL (8 HR.TWA) = 15 MG/M3 ACGIH-TLV (TWA) = 10 MG/M3 IARC RATING = 2B (POSSIBLY CARCINOGENIC TO HUMANS)	13463-67-7	6.549
H TRIETHYLAMINE ACGIH-TLV (TWA) = 10 PPM ACGIH-STEL = 15 PPM OSHA-PEL (8 HR. TWA) = 10 PPM OSHA-STEL (30 MIN.) = 15 PPM	121-44-8	1.10

DESCRIPTION OF POSSIBLE COMPONENT PREFIXES ABOVE:

H--This item is defined as a HAP (Hazardous Air Pollutant) by the Clean Air Act.

P--This item is defined as a TAP (Toxic Air Pollutant) by the Jefferson County (Louisville, KY) Air Pollution Control District.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 0 - 192
VOC EXCL. EXEMPT: 1.656
WT./GAL.: 9.009 lb/gal

SPECIFIC GRAVITY (H2O=1): 1.082
VOC INCL. EXEMPT: 0.759 lb/gal
VOLATILE WT%: 58.233

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

ACTUAL FLASHPOINT (AS APPLICABLE): 200
LOWEST FLASHPOINT: 20

METHOD USED: PENSKY MARTENS
METHOD USED: LOWEST INGREDIENT

EXTINGUISHING MEDIA:

Use CO2, Dry Chemical, Foam, Alcohol Foam or Water Fog.

SPECIAL FIREFIGHTING PROCEDURES

Clear fire area of unprotected personnel. Containers that are exposed to intense heat should be cooled with water. Avoid spreading burning liquid with the water used for cooling purposes. Do not enter fire area without protective gear. Fight fire from safe distance or a protected location.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Vapors may be heavier than air and may travel along the ground before ignition/flashing back to vapor source. Keep welding or cutting equipment away from product.

***** NOTICE: All health and safety statements contained in this MSDS relate to the individual components, not the product as a whole. ALWAYS REFER TO THE MOST SEVERE STATEMENT IN THAT SECTION! *****

SECTION V - REACTIVITY DATA

STABILITY

This product is stable.

CONDITIONS TO AVOID

Avoid exposure to sparks, open flame, hot surfaces and all sources of heat ignition.

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid contact with strong oxidizing agents, strong mineral acids.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, etc.

HAZARDOUS POLYMERIZATION

Hazardous polymerization will not occur.

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation in high concentrations of vapor may cause mucous membrane irritation and narcosis (sleepiness, drowsiness, etc.) Inhalation will cause irritation of the mucous membranes of the respiratory tract.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eye contact causes severe damage and even blindness very rapidly, vapors can cause severe irritation, redness, tearing, blurred vision and a sensation of seeing halos around lights. Skin contact can cause slight irritation. Prolonged skin contact can cause dermatitis and burns. Can be absorbed through the skin in toxic amounts, especially from prolonged or repeated exposure.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No information available or not applicable.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Has apparently been found to cause liver abnormalities, kidney abnormalities, kidney damage, eye damage or lung damage in laboratory animals. NOTICE--Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after applicable limits. Follow respirator manufacturer's directions for respirator use.

No information available or not applicable.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush with lukewarm water for 15 minutes. Seek a physician immediately or call emergency number listed

in Section I.

SKIN CONTACT: Remove contaminated clothing promptly and rinse effected areawith plenty of water. Launder contaminated clothing before reuse. Contact a physician immediately or call emergency number listed in Section I.

INHALATION: Remove exposed individual to fresh air. Restore breathing if required. Contact a physician immediately or call emergency number listed inSection I.

INGESTION: Rinse mouth immediately. Give exposed individual 6 to 8 ounces of liquid if individual can swallow. (Never give anything by mouth to an unconscious person.) **DO NOT INDUCE VOMITING** unless advised by a physician. Contact a physician immediately or call emergency number listed in Section I.

===== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shut off and eliminate all ignition sources. Stay upwind and away from spill unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Cover with inert material to reduce fumes. Keep out of drains, sewers or waterways. Contact fire authorities. Notify local health and pollution agencies. Call spill response teams.

WASTE DISPOSAL METHOD

Dispose of product in accordance with applicable local, county, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid skin contact and inhalation of vapors or mist if generated.

OTHER PRECAUTIONS

No information available or not applicable.

===== **SECTION VIII - CONTROL MEASURES** =====

RESPIRATORY PROTECTION

In outdoor or open areas use (NIOSH/MSHA approved) mechanical filter respirator to remove solid airborne particles of overspray during spray application. In restricted ventilation areas use (NIOSH/MSHA approved) chemical-mechanical filters designed to remove a combination of particulate and gas and vapor. In confined areas use (NIOSH/MSHA approved) air line type respirators or hoods. Respiratory protection may also be necessary in any later manufacturing operations in which the product may become airborne - in the form of vapor or dust.

VENTILATION

Use ventilation as required to control vapor/dust concentrations. Avoid prolonged or repeated breathing of vapors/dust. If exposures exceed TLV, use NIOSH approved respirator to prevent overexpsures.

PROTECTIVE GLOVES

Protective gloves are required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact. (Consult your safety equipment supplier.)

EYE PROTECTION

Avoid contact with eyes. Wear goggles if there is a likelihood of contact with eyes. (Consult your safety equipment supplier.) Eyewash stations and safety showers should be readily available in use and handling areas.

Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

WORK/HYGIENIC PRACTICES

YARBUS PAINT COMPANY takes no responsibility for determining what measures are required for personal protection in any specific application. Wash hands thoroughly before eating and using the restroom.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS INFORMATION RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES AND IS BELIEVED TO BE RELIABLE. MARCUS PAINT COMPANY MAKES NO EXPRESS OR IMPLIED WARRANTIES REGARDING THE ACCURACY HEREOF OR THE SUITABILITY OF THE PRODUCT FOR ANY APPLICATION BY THE USER. INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE.